



Technical details

Product version:	4.5
Approvals:	CE;cULus Listed;TÜV;BG
Number of SafetyBUS p interfaces:	1
Number of PROFIBUS-DP interfaces:	1
Type of digital inputs:	FS standardised input
Application in accordance with:	DIN V 19250;DIN VDE 0116, 0;EN 954-1
Protection type, housing:	IP20
Width dimension:	123.0 mm
Height dimension:	246.0 mm
Depth dimension:	161.0 mm
Gross weight:	3320 g
Net weight:	2054 g
Ambient temperature:	0 - 60 °C

Accessories



300914

PSS ZKL 3006-3



300916

PSS ZKF 3006-3



301288B

Basic License for PSS WIN-PRO Full



301288K

User License for PSS WIN-PRO Full



301288M

Multi User License for PSS WIN-PRO Full



301289B

Basic License for PSS WIN-PRO Service



301289K

User License for PSS WIN-PRO Service



301289M

Multi User License for PSS WIN-PRO Serv



301960

PSS PG CAB RS232 spez.



305159

PSS Conv RS 232 / RS 485



305161

PSS Conv USB / RS 485



310300

Serial programming cable



311080

PSS SB PG ADAPTER



374205

H-P10 C485 Cable PC-CPU
