

PNOZ m1p base unit

773100



Technical details

Product version:	6.7
Approvals:	CE;cULus Listed;TÜV;BG;KOSHA;CCC;KCC
Base unit:	Yes
Number of digital inputs:	20
Number of test pulse outputs:	4
Number of semiconductor outputs:	4
Number of relay outputs cat.2:	2
No. of relay outputs, Cat.4:	1
Number of cascading outputs:	1
Supply voltage (V):	24,0
Supply voltage type:	DC
Permitted number of expansion modules:	8
Number of RS 232 interfaces:	1
Terminal type:	Screw terminal;Spring-loaded terminal
Version for extreme environ. conditions:	Standard
Width dimension:	135.0 mm
Height dimension:	94.0 mm
Depth dimension:	121.0 mm
Gross weight:	519 g
Net weight:	499 g

Ambient temperature:

0 - 60 °C

Accessories

773010B

Basic License for PNOZmulti Config.



779201

PNOZmulti Chipcard 1 piece 8kb



779211

Chipcard 1 piece 32kB

783100

PNOZ m1p Set spring loaded terminals



793100

PNOZ m1p/m0p plug in screw terminals


Related Products

773010L

Lite License for PNOZmulti Config.

773011L

Lite License for PNOZmulti Service



774639

KOP-XE



779000

PNOZmulti Tool Kit



779110

PNOZmulti Bus-Terminator



779200

PNOZmulti Chipcard Set 10 piece 8KB



779212

PNOZmulti Chipcard Set 10 pieces 32kB



779230

Chip Card Reader



779240

PNOZmulti Chipcard Holder (Sparepart)



779250

PNOZmulti Seal 12 pieces
