



Technical details

Product version:	3.4
Approvals:	CE;cULus Listed;TÜV;BG
Application range:	Standard/failsafe
Number of SafetyBUS p interfaces:	1
Number of PROFIBUS-DP interfaces:	1
Permitted number of expansion modules:	64
Number of USB slave interfaces:	1
Protection type, housing:	IP20
Width dimension:	75.2 mm
Height dimension:	128.4 mm
Depth dimension:	79.4 mm
Gross weight:	234 g
Net weight:	201 g
Ambient temperature:	0 - 60 °C

Accessories

311070

PSS SB BUSCABLE

311071

PSS SB BUSCABLE0 MOVE

311074

PSS SB BUSCABLE LC



311040

PSS SB SUB-D4



311041

PSS SB SUB-D4-DIAG



312190

PSSu E F PS



311050

PSS SB SUB-D0



312191

PSSu E F PS1



311051

PSS SB Sub-D 1 Connector



311053

PSS SB SUB-D-FO HIGH SPEED



311054

PSS SB SUB-D1-DIAG



311058

PSS SB SUB-D3



312650

PSSu BS 1/8 S



312651

PSSu BS 1/8 C



312656

PSSu BS 2/8 S



312657

PSSu BS 2/8 C

Related Products

312890

PSSu Assistant & Startup tool CD-ROM



312900

PSSu A ET (10 pcs.)



312901

PSSu A ETM (2 pcs.)



312902

PSSu A EC



312949

PSSu A ET PE (10 pcs.)



312958

PSSu A LA0 (10 x 108 pcs.)



312963

PSSu A SH S (10 pcs.)



312964

PSSu A SH T (10 pcs.)



312967

PSSu A LA0.1 (10 x 108 pcs.)



312992

PSSu A USB-CAB03
